

DURA BUILD CARE PVT. LTD.



AN ISO 9001 : 2008 COMPANY

“Quality, Integrity Assured.”

DURACRYL MP

Ready to use Acrylic sealant

Description :

Single pack ready to use multi purpose Sealant. **DURACRYL MP** is a compound on water based acrylic. It is available in grey colour. Any other colour is available on request.

Use :

DURACRYL MP is extensively used to fill gaps and joints internally subject to a limited amount of movement e.g. around doors, window, fixtures and fittings. It is found to be excellent as joint filler between different building materials.

Features :

- Excellent adhesion to the most building materials.
- No mixing – ready to use directly from the cartridge/container.
- Odourless – may be over painted.
- Highly UV – resistant.
- Not suitable on soft plastic, bare materials, bitumen or tar and also under water joints.

Application :

After thorough priming with primer apply **DURACRYL MP** straight from the container. Finishing may be carried out by using portable water/primer.



Technical Data :

DURACRYL MP is grey in colour. Other colours are available on request.

Movement	: 10 to 15% of average joint width.
Minimum joint depth	: 6mm
Maximum joint width	: 25mm
Width	: Depth ratio for joints upto 10mm wide: 1 : 1 Width : Depth ratio for joints between 10mm to 25mm. wide 2:1
Density	: 1.6 ± 0.1 Kg/L at 27 ⁰ C
Application temperature	: Between 5 ⁰ C and 45 ⁰ C
Priming	: Use Duracryl MP Primer for all surfaces @ coverage 4 to 7 m ² per Kg.
Shelf Life	: One year if kept unopened
Storage	: Keep it in a cool place.
Curing	: Full cure approx. 10 days. (Depending upon temperature and humidity)
Packing	: 1 Kg, 5 Kg and 30 Kg container.

IMPORTANT: Though the product may change with some code as suffix or addendum to the principal or original name out of some minor adjustment and fine tuning in the formulation due to our continuous research and development but shall exhibit the stated properties with more improvement.

WARRANTY: Our high potency products are manufactured under stringent National/International Quality Standard specifications and guaranteed against any manufacturing defect. Suggestions and recommendations are made here based on our most practical experience and exposure over 25 years in the field and are believed to be most appropriate and correct BUT no liability can be accepted by us, as the conditions of use of such products are beyond our control.

HEAD OFFICE: 104-106, Dimension Deepti Plaza, Plot No-3, LSC, Pocket-6, Nasirpur, Dwarka, New Delhi-110045.

Phone No.: 011-25050236, 011-25050237, Fax No.: 011-25050238

E-mail: admin@durabuildcare.com, sales@durabuildcare.com, Website: durabuildcare.com