



DURASILFIL 2P

A Crack Filling & Sealing Compound in Two Packs

Description :

DURASILFIL 2P is an easy to use filling / sealing material based on polymer modified cementitious product. It is available in cement grey colour and two pack system.

Uses :

DURASILFIL 2P is suitable for any crack filling upto 6 mm width and also for sealing joint. It is equally suitable for sealing joints of all types of sanitary ware specially in the collar type of sanitary fitting. In joints of cast iron, asbestos cement, stone ware, ceramic, clay storm water drain and down-take pipes. It is most useful in sealing / filling cracks of masonry / concrete surfaces.

Features :

- Flexible – Can accommodate movement.
- Non-shrink. No crack.
- Seepage / leakage through the cracks / joints is permanently sealed - waterproof.
- Adhesion is superb in all building substrates.
- Easy application.

Application :

Cracks filling : Surface should be clean and free from all dirt, dusts, loosely adhering particles, oils & grease.

Joint sealing : Joint surfaces should also be cleaned in the same way as above.

The **DURASILFIL 2P** powder of Pack B should be mixed with **DURASILFIL 2P** Liquid Pack A in the proportion of 1:4 by wt. parts. A little more liquid of Pack A may be required to get smooth flow-able consistency for filling cracks and sealing joints also. On an average, 1 kg mixed material of **DURASILFIL 2P** covers around 0.5 to 0.7 m² with 1mm thickness.

Technical Data :

| | | |
|-----------------|---|--|
| Mix Ratio | : | Liquid Pack A : 1 kg, Powder Pack B : 4kg i.e. Pack A : Pack B = 1 : 4 by wt. |
| Coverage | : | 0.5 to 0.7 m ² per kg of mixed material with 1 mm thickness. |
| Shelf life | : | 6 months if kept in original packing under shed. |
| Storage | : | Keep it in a dry place. |
| Packing | : | Pack A : 5 kg Poly container; Pack B: 20 kg Poly Sack. |
| Health & Safety | : | Non-flammable, Non-hazardous |



IMPORTANT: Though the product may change with some code as suffix or addendum to the principal or original name out of some minor adjustment and fine tuning in the formulation due to our continuous research and development but shall exhibit the stated properties with more improvement.

WARRANTY: Our high potency products are manufactured under stringent National/International Quality Standard specifications and guaranteed against any manufacturing defect. Suggestions and recommendations are made here based on our most practical experience and exposure over 25 years in the field and are believed to be most appropriate and correct BUT no liability can be accepted by us, as the conditions of use of such products are beyond our control.

HEAD OFFICE: 104-106, Dimension Deepti Plaza, Plot No-3, LSC, Pocket-6, Nasirpur, Dwarka, New Delhi-110045.

Phone No.: 011-25050236, 011-25050237, Fax No.: 011-25050238

E-mail: admin@durabuildcare.com, sales@durabuildcare.com, Website: durabuildcare.com