

DURA BUILD CARE PVT. LTD.



AN ISO 9001 : 2008 COMPANY

"Quality, Integrity Assured."

DURAXYFLOR SL

Shelf leveling 2 mm Epoxy Floor

Description :

Solvent less 3 pack self leveling epoxy floor topping system with chemical and abrasion resistant property. The system includes a two pack epoxy resin primer i.e. **Duraxy P**.

Uses :

Shelf leveling 2 mm epoxy mortar for seamless floor toppings in industries with medium degree of exposure, like power plants, exhibition halls, shops, pharmaceutical industries, laboratories, clean rooms, on cementitious floors etc.

Features :

- ❖ High mechanical strength-hard wearing and durable.
- ❖ Good abrasion resistance
- ❖ Chemical resistance-most industrial chemicals
- ❖ Shelf leveling, smooth, glossy and hygienic seamless surface
- ❖ High impermeability
- ❖ Easy to lay-consistent quality

Application :

Mix Pack A and Pack B to a smooth consistency and finally within next 5 mins mix Pack C into it till uniform flowable epoxy mortar results. Then spread it with bedding comb on a primer applied even and tacky surface and detrain entrapped air, if any, with spiked roller.



Technical Data :

Pack A	: White Base
Pack B	: Black hardener
Pack C	: Filler

Mixed material will be smooth grey. Such grey material is also supplied in two packs. Other colors can also be produced against specific requirements.

S.G. at 27 ⁰ C	: 1700
Coverage	: 3.20 to 3.80 Kg/m ² for 2mm thickness
Duraxy P	: 4 to 5 m ²
Min application Temp.	: 5 ⁰ C
Pot Life at 25 ⁰ C	: 60 minutes
30 ⁰ C	: 40 minutes
35 ⁰ C	: 40 minutes
40 ⁰ C	: 25 minutes
Shelf Life	: 12 months if kept in original packing under shed.
Packing	: 4 Kg in proportionate Pack A, B & C
Storage	: Keep in a cool place
Health & Safety	: Use protective clothing & eye goggles while handling these materials. Do not smoke and use naked flame nearby as it is inflammable.

IMPORTANT: Though the product may change with some code as suffix or addendum to the principal or original name out of some minor adjustment and fine tuning in the formulation due to our continuous research and development but shall exhibit the stated properties with more improvement.

WARRANTY: Our high potency products are manufactured under stringent National/International Quality Standard specifications and guaranteed against any manufacturing defect. Suggestions and recommendations are made here based on our most practical experience and exposure over 25 years in the field and are believed to be most appropriate and correct BUT no liability can be accepted by us, as the conditions of use of such products are beyond our control.

HEAD OFFICE: 104-106, Dimension Deepti Plaza, Plot No-3, LSC, Pocket-6, Nasirpur, Dwarka, New Delhi-110045.

Phone No.: 011-25050236, 011-25050237, Fax No.: 011-25050238

E-mail: admin@durabuildcare.com, sales@durabuildcare.com, Website: durabuildcare.com